

1432/4.16.689.771

DESCRIPTION

TECHNICAL DATA AND DIMENSIONS

| | | | | | | | |
|------------------|-------|-----|-----|-------------------------------------|---------------|-----|-------|
| Series | 1432 | | | No. of starts | 1 | | |
| Nominal diameter | [mm] | dN | 16 | Friction torque FROM | [Ncm] | 1,4 | |
| Lead | [mm] | P | 4 | Friction torque TO | [Ncm] | 1,4 | |
| Shaft style | B | | | Accuracy | T | | |
| Nominal stroke | [mm] | 600 | | Preload/backlash free/with backlash | with backlash | | |
| Overall length | [mm] | G1 | 771 | Nut length | [mm] | L | 38 |
| Thread length | [mm] | G2 | 689 | Dynamic load capacity | [kN] | Ca | 8,90 |
| Ball circles | i | | 1x3 | Static load capacity | [kN] | C0a | 11,40 |
| Ball diameter | [mm] | dW | 3 | Pilot diameter | [mm] | D1 | 28 |
| DN-value | 68800 | | | | | | |

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws