

3526/40.50.7,5.3NE

DESCRIPTION

- **ETA+ Nut Series** with **external ball return**
- Flange nut with wipers on both ends
- Product photo shows combination wipers
- Nut shape according to DIN for assembly by flange
- Multiple start ball thread, ground execution according to accuracy class P1 - P5



TECHNICAL DATA AND DIMENSIONS

Series			3526	Friction torque FROM		[Ncm]	41,1
Nominal diameter	[mm]	dN	50	Friction torque TO		[Ncm]	85,5
Lead	[mm]	P	40	Accuracy			P
Ball circles		i	3+3	Nut length		[mm]	L 149
Ball diameter	[mm]	dW	7,5	Dynamic load capacity		[kN]	Ca 63,30
DN-value			160000	Static load capacity		[kN]	C0a 95,90
No. of starts			2	Pilot diameter		[mm]	D1 82

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws