



1530/1.12.260.330

DESCRIPTION

TECHNICAL DATA AND DIMENSIONS

Series	1530			No. of starts	1		
Nominal diameter	[mm]	dN	12	Friction torque FROM	[Ncm]	1,0	
Lead	[mm]	P	1	Friction torque TO	[Ncm]	2,0	
Shaft style	B			Accuracy	T		
Nominal stroke	[mm]	200		Preload/backlash free/with backlash	Preload		
Overall length	[mm]	G1	330	Nut length	[mm]	L	49
Thread length	[mm]	G2	260	Dynamic load capacity	[kN]	Ca	1,05
Ball circles	i		2x2	Static load capacity	[kN]	C0a	1,63
Ball diameter	[mm]	dW	1	Pilot diameter	[mm]	D1	24
DN-value	24000						

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws