

1530/1.12.410.480

---

DESCRIPTION

---

TECHNICAL DATA AND DIMENSIONS

---

Series			1530	No. of starts			1
Nominal diameter	[mm]	dN	12	Friction torque FROM	[Ncm]		1,0
Lead	[mm]	P	1	Friction torque TO	[Ncm]		2,0
Shaft style			B	Accuracy			T
Nominal stroke	[mm]		350	Preload/backlash free/with backlash			Preload
Overall length	[mm]	G1	480	Nut length	[mm]	L	49
Thread length	[mm]	G2	410	Dynamic load capacity	[kN]	Ca	1,05
Ball circles		i	2x2	Static load capacity	[kN]	C0a	1,63
Ball diameter	[mm]	dW	1	Pilot diameter	[mm]	D1	24
DN-value			24000				

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | [info@steinmeyer.com](mailto:info@steinmeyer.com)

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws