

# 1132/1.8.140.198

---

DESCRIPTION

---

TECHNICAL DATA AND DIMENSIONS

---

|                  |      |    |        |                                     |  |  |               |
|------------------|------|----|--------|-------------------------------------|--|--|---------------|
| Series           |      |    | 1132   | No. of starts                       |  |  | 1             |
| Nominal diameter | [mm] | dN | 8      | Friction torque FROM                |  |  | [Ncm] 0,5     |
| Lead             | [mm] | P  | 1      | Friction torque TO                  |  |  | [Ncm] 0,5     |
| Shaft style      |      |    | B      | Accuracy                            |  |  | T             |
| Nominal stroke   | [mm] |    | 100    | Preload/backlash free/with backlash |  |  | with backlash |
| Overall length   | [mm] | G1 | 198    | Nut length                          |  |  | [mm] L 22     |
| Thread length    | [mm] | G2 | 140    | Dynamic load capacity               |  |  | [kN] Ca 1,21  |
| Ball circles     |      | i  | 1x3    | Static load capacity                |  |  | [kN] C0a 1,51 |
| Ball diameter    | [mm] | dW | 1      | Pilot diameter                      |  |  | [mm] D1 16,5  |
| DN-value         |      |    | 120000 |                                     |  |  |               |

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | [info@steinmeyer.com](mailto:info@steinmeyer.com)

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws