1132/2,5.8.80.138

DESCRIPTION

TECHNICAL DATA AND DIMENSIONS

Series			1132	No. of starts			1
Nominal diameter	[mm]	dN	8	Friction torque FROM	[Ncm]		0,5
Lead	[mm]	P	2,5	Friction torque TO	[Ncm]		0,5
Shaft style			B	Accuracy			T
Nominal stroke	[mm]		40	Preload/backlash free/with backlash			with backlash
Overall length	[mm]	G1	138	Nut length	[mm]	L	29
Thread length	[mm]	G2	80	Dynamic load capacity	[kN]	Ca	2,00
Ball circles		i	1x3	Static load capacity	[kN]	C0a	2,10
Ball diameter	[mm]	dW	1,5	Pilot diameter	[mm]	D1	16,5
DN-value			120000				

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws