
1112/0,5.8.80.138


DESCRIPTION

- Nut Series 1112 with internal ball return, Cylindrical nut with connecting thread and 4-point-contact, without wipers
- Single start ball thread, ground execution
  according to accuracy class P1 - P5
- Miniature ball screws also available with axial play



TECHNICAL DATA AND DIMENSIONS


L
L2
HS
D2
D1


G1
G2
9
10
9
18
8
(4)
6
4
Ø5,7x0,8
Ø6h6
M8x1
Ø8g5
Ø11,5
SW10
Ø8h8
Ø6g6

Series			1112	No. of starts			1
Nominal diameter	[mm]	dN	8	Friction torque FROM	[Ncm]		0,5
Lead	[mm]	P	0,5	Friction torque TO	[Ncm]		0,5
Shaft style			B	Accuracy			P
Nominal stroke	[mm]		40	Preload/backlash free/with backlash			with backlash
Overall length	[mm]	G1	138	Nut length	[mm]	L	21
Thread length	[mm]	G2	80	Dynamic load capacity	[kN]	Ca	0,40
Ball circles		i	1x3	Static load capacity	[kN]	C0a	0,50
Ball diameter	[mm]	dW	0,6	Pilot diameter	[mm]	D1	16,5
DN-value			120000				

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws