

# 1132/1.12.210.280

---

DESCRIPTION

---

TECHNICAL DATA AND DIMENSIONS

---

Series			1132	No. of starts			1
Nominal diameter	[mm]	dN	12	Friction torque FROM	[Ncm]	1,0	
Lead	[mm]	P	1	Friction torque TO	[Ncm]	1,0	
Shaft style			B	Accuracy			T
Nominal stroke	[mm]	150		Preload/backlash free/with backlash			with backlash
Overall length	[mm]	G1	280	Nut length	[mm]	L	24
Thread length	[mm]	G2	210	Dynamic load capacity	[kN]	Ca	1,49
Ball circles	i		1x3	Static load capacity	[kN]	C0a	2,45
Ball diameter	[mm]	dW	1	Pilot diameter	[mm]	D1	20,5
DN-value			120000				

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | [info@steinmeyer.com](mailto:info@steinmeyer.com)

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws