

3526/35.50.7,5.4NE

DESCRIPTION

- **ETA+ Nut Series** with **external ball return**
- Flange nut with wipers on both ends
- Product photo shows combination wipers
- Nut shape according to DIN for assembly by flange
- Multiple start ball thread, ground execution according to accuracy class P1 - P5



TECHNICAL DATA AND DIMENSIONS

Series			3526	Nut length	[mm]	L	170
Nominal diameter	[mm]	dN	50	Flange thickness	[mm]	L7	16
Lead	[mm]	P	35	Dynamic load capacity	[kN]	Ca	85,40
Ball circles		i	4+4	Static load capacity	[kN]	C0a	135,20
Ball diameter	[mm]	dW	7,5	Pilot diameter	[mm]	D1	82
DN-value			160000	Pilot diameter tolerance	[mm]		g6
No. of starts			2	Bolt circle diameter	[mm]	D4	100
Friction torque FROM	[Ncm]		55,5	Flange hole diameter		D5	11
Friction torque TO	[Ncm]		115,3	Flange diameter	[mm]	D6	118
Pilot Length	[mm]	L1	25	Flange flat dimension	[mm]	H	46
Accuracy			P	Lube hole	[mm]	DS	M8x1

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws