

# 1432/4.12.355.397

---

DESCRIPTION

---

TECHNICAL DATA AND DIMENSIONS

---

Series			1432	Friction torque TO		[Ncm]	1,0
Nominal diameter	[mm]	dN	12	Accuracy			T
Lead	[mm]	P	4	Preload/backlash free/with backlash			with backlash
Shaft style			A	Nut length		[mm]	L 36
Nominal stroke	[mm]		300	Dynamic load capacity		[kN]	Ca 3,60
Overall length	[mm]	G1	397	Static load capacity		[kN]	C0a 4,30
Thread length	[mm]	G2	355	Pilot diameter		[mm]	D1 22
Ball circles		i	1x3	Pilot diameter tolerance		[mm]	g6
Ball diameter	[mm]	dW	2	Bolt circle diameter		[mm]	D4 29
DN-value			54000	Flange diameter		[mm]	D6 37
No. of starts			1	Flange flat dimension		[mm]	H 12
Friction torque FROM		[Ncm]	1,0				

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | [info@steinmeyer.com](mailto:info@steinmeyer.com)

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws