2442/10.16.139.221

DESCRIPTION

TECHNICAL DATA AND DIMENSIONS

Series			2442	Pilot Length	[mm]	L1	13
Nominal diameter	[mm]	dN	16	Accuracy			T
Lead	[mm]	P	10	Preload/backlash free/with backlash			backlash free
Shaft style			B	Nut length	[mm]	L	64
Nominal stroke	[mm]		50	Wiper extension	[mm]	L3	12
Overall length	[mm]	G1	221	Flange thickness	[mm]	L7	10
Thread length	[mm]	G2	139	Dynamic load capacity	[kN]	Ca	31,40
Ball circles		i	5+5	Static load capacity	[kN]	C0a	47,80
Ball diameter	[mm]	dW	3,5	Pilot diameter	[mm]	D1	32
DN-value			68800	Pilot diameter tolerance	[mm]		g6
No. of starts			2	Bolt circle diameter	[mm]	D4	42
Friction torque FROM	[Ncm]		4,0	Flange diameter	[mm]	D6	52
Friction torque TO	[Ncm]		4,0	Flange flat dimension	[mm]	H	20

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws