

1516/5.50.3,5.4

DESCRIPTION

- Nut Series 1516 with [internal ball return](#), Flange double nut with 2-point-contact, with standard synthetic wipers on both ends
- Nut shape according to DIN for assembly by flange
- Single start ball thread, ground execution according to accuracy class P1 - P5



TECHNICAL DATA AND DIMENSIONS

Series			1516	Flange thickness	[mm]	L7	16
Nominal diameter	[mm]	dN	50	Dynamic load capacity	[kN]	Ca	25,10
Lead	[mm]	P	5	Static load capacity	[kN]	C0a	65,20
Ball circles		i	2x4	Ball diameter	[mm]	dW	3,5
Additional wiper extensions for combination wipers	[mm]	LA	9	DN-value			120000
Pilot Length	[mm]	L1	10	No. of starts			1
Pilot diameter	[mm]	D1	75	Stiffness	[N/μm]	Rnu,ar	1070
Pilot diameter tolerance	[mm]		g6	Friction torque FROM	[Ncm]		30,1
Bolt circle diameter	[mm]	D4	93	Friction torque TO	[Ncm]		70,3
Flange hole diameter		D5	11	Max. preload	[kN]		2,51
Lube hole	[mm]	DS	M8x1	Accuracy			P
Flange diameter	[mm]	D6	110	Nut length	[mm]	L	101
Flange flat dimension	[mm]	H	42,5	Wiper extension	[mm]	L3	6

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws