
1516/15.40.7,5.4E

DESCRIPTION

- ETA+ Nut Series with internal ball return
- Flange nut, with standard wipers on both ends
- Nut shape according to DIN for assembly by flange
- Single start ball thread, ground execution according to accuracy class P1 - P5



TECHNICAL DATA AND DIMENSIONS


A oder LA
A or LA
L
A oder LA
A or LA
L3
L7
L1
A
D6
D4
D1 ±0,5
Wiper
Abstreifer
Abstreifer
Wiper
D1 g6
D1-1
90°
45°
15°
D5
Ansicht "A"
View "A"
DS
30°
H
H
Form B
Shape B

Series			1516	Flange thickness	[mm]	L7	14
Nominal diameter	[mm]	dN	40	Dynamic load capacity	[kN]	Ca	76,90
Lead	[mm]	P	15	Static load capacity	[kN]	C0a	103,40
Ball circles		i	2x4	Ball diameter	[mm]	dW	7,5
Additional wiper extensions for combination wipers	[mm]	LA	12	DN-value			120000
Pilot Length	[mm]	L1	16	No. of starts			1
Pilot diameter	[mm]	D1	63	Stiffness	[N/µm]	Rnu,ar	830
Pilot diameter tolerance	[mm]		g6	Friction torque FROM	[Ncm]		40,0
Bolt circle diameter	[mm]	D4	78	Friction torque TO	[Ncm]		83,1
Flange hole diameter		D5	9	Max. preload	[kN]		7,69
Lube hole	[mm]	DS	M8x1	Accuracy			P
Flange diameter	[mm]	D6	93	Nut length	[mm]	L	211
Flange flat dimension	[mm]	H	35	Wiper extension	[mm]	L3	7

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws