

1214/5.16.889.971

DESCRIPTION

- Nut Series 1214 with internal ball return
- Cylindrical nut with 4-point-contact, without wipers
- Nut shape design for assembling in a housing
- Single start ball thread, ground execution according to accuracy class P1 - P5
- Miniature ball screws also available with axial play



TECHNICAL DATA AND DIMENSIONS


L
AP
LP
TP
BP
D1
G1
G2
22
15
10
20
10
5
5
8
Ø9,6x1,15
Ø10h6
M12x1
Ø12g5
SW13
Ø15,5h8
Ø10g6

Series			1214	Friction torque TO	[Ncm]		4,0
Nominal diameter	[mm]	dN	16	Accuracy			P
Lead	[mm]	P	5	Nut length	[mm]	L	27
Ball circles		i	1x3	Dynamic load capacity	[kN]	Ca	10,10
Ball diameter	[mm]	dW	3,5	Static load capacity	[kN]	C0a	12,00
DN-value			120000	Pilot diameter	[mm]	D1	28
No. of starts			1	Pilot diameter tolerance	[mm]		h6
Friction torque FROM	[Ncm]		4,0				

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws