

1132/5.16.889.971

DESCRIPTION

TECHNICAL DATA AND DIMENSIONS

| | | | | | | | |
|------------------|------|----|--------|-----------------------|-------|-----|-------|
| Series | | | 1132 | Friction torque FROM | [Ncm] | 4,0 | |
| Nominal diameter | [mm] | dN | 16 | Friction torque TO | [Ncm] | 4,0 | |
| Lead | [mm] | P | 5 | Accuracy | | | T |
| Ball circles | | i | 1x3 | Nut length | [mm] | L | 43 |
| Ball diameter | [mm] | dW | 3,5 | Dynamic load capacity | [kN] | Ca | 10,10 |
| DN-value | | | 120000 | Static load capacity | [kN] | C0a | 12,00 |
| No. of starts | | | 1 | Pilot diameter | [mm] | D1 | 28,5 |

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws