

2442/30.16.470.527

DESCRIPTION

TECHNICAL DATA AND DIMENSIONS

Series			2442	Wiper extension	[mm]	L3	12
Nominal diameter	[mm]	dN	16	Dynamic load capacity	[kN]	Ca	5,90
Lead	[mm]	P	30	Static load capacity	[kN]	C0a	7,60
Ball circles		i	1+1	Pilot diameter	[mm]	D1	32
Ball diameter	[mm]	dW	3,5	Pilot diameter tolerance	[mm]		g6
DN-value			68800	Bolt circle diameter	[mm]	D4	42
No. of starts			2	Flange hole diameter		D5	5,5
Friction torque FROM	[Ncm]		4,0	Lube hole	[mm]	DS	M6x1
Friction torque TO	[Ncm]		4,0	Flange diameter	[mm]	D6	52
Accuracy			T	Flange flat dimension	[mm]	H	20
Nut length	[mm]	L	73				

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws