
2526/15.25.3,5.2E


DESCRIPTION

- ETA+ Nut Series with end cap ball return
- Flange nut with standard wipers on both ends
- Nut shape according to DIN for assembly by flange
- Multiple start ball thread, ground execution according to accuracy class P1 - P5



TECHNICAL DATA AND DIMENSIONS





Ansicht "A"
View "A"

Form B
Shape B

Series			2526	Flange thickness	[mm]	L7	10
Nominal diameter	[mm]	dN	25	Dynamic load capacity	[kN]	Ca	10,70
Lead	[mm]	P	15	Static load capacity	[kN]	C0a	13,30
Ball circles		i	2+2	Ball diameter	[mm]	dW	3,5
Additional wiper extensions for combination wipers	[mm]	LA	-	DN-value			160000
Pilot Length	[mm]	L1	16	No. of starts			2
Pilot diameter	[mm]	D1	40	Stiffness	[N/µm]	Rnu,ar	250
Pilot diameter tolerance	[mm]		g6	Friction torque FROM	[Ncm]		1,1
Bolt circle diameter	[mm]	D4	51	Friction torque TO	[Ncm]		9,6
Flange hole diameter		D5	6,6	Max. preload	[kN]		1,07
Lube hole	[mm]	DS	M6x1	Accuracy			P
Flange diameter	[mm]	D6	62	Nut length	[mm]	L	48
Flange flat dimension	[mm]	H	24	Wiper extension	[mm]	L3	7

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws