
2426/15.25.3,5.4


DESCRIPTION

- Nut Series 2426 with end cap ball return, Flange single nut with 4-point-contact with standard synthetic wipers on both ends
- Nut shape according to DIN for assembly by flange
- Multiple start ball thread, ground execution according to accuracy class P1 - P5



TECHNICAL DATA AND DIMENSIONS





Ansicht "A"
View "A"

Form B
Shape B

Series			2426	Nut length	[mm]	L	48
Nominal diameter	[mm]	dN	25	Wiper extension	[mm]	L3	7
Lead	[mm]	P	15	Flange thickness	[mm]	L7	10
Ball circles		i	2+2	Dynamic load capacity	[kN]	Ca	16,80
Ball diameter	[mm]	dW	3,5	Static load capacity	[kN]	C0a	28,60
DN-value			160000	No. of starts			2
Additional wiper extensions for combination wipers	[mm]	LA	-	Stiffness	[N/µm]	Rnu,ar	270
Pilot Length	[mm]	L1	16	Pilot diameter	[mm]	D1	40
Pilot diameter tolerance	[mm]		g6	Bolt circle diameter	[mm]	D4	51
Flange hole diameter		D5	6,6	Max. preload	[kN]		1,344
Flange diameter	[mm]	D6	62				

August Steinmeyer GmbH & Co. KG | Riedstraße 7 | 72458 Albstadt | Phone +49 (0) 7431 1288-0 | Fax +49 (0) 7431 1288-89 | info@steinmeyer.com

Drive Technology, Ball Screws, Precision Ball Screws, Miniature Ball Screws, Ultra Thrust Ball Screws, Rotating Nuts, Cooled Ball Screws, Precision Lead Screws, Differential Rolled Screws, Rolled Ball Screws